



MATERIAL SAFETY DATA SHEET

Sikadur Injection Gel / Anchor Fix 4 - Part B

HMIS

HEALTH	*3
FLAMMABILITY	1
REACTIVITY	0
PERSONAL PROTECTION	D

1. Product And Company Identification

Supplier

Sika Corporation
201 Polito Ave
Lyndhurst, NJ 07071

Company Contact: EHS Department
Telephone Number: 201-933-8800
FAX Number: 201-933-9379
Web Site: www.sikausa.com

Manufacturer

Sika Corporation
201 Polito Ave
Lyndhurst, NJ 07071

Company Contact: EHS Department
Telephone Number: 201-933-8800
FAX Number: 201-933-9379
Web Site: www.sikausa.com

Supplier Emergency Contacts & Phone Number

CHEMTREC: 800-424-9300
INTERNATIONAL: 703-527-3887

Manufacturer Emergency Contacts & Phone Number

CHEMTREC: 800-424-9300
INTERNATIONAL: 703-527-3887

Issue Date: 08/14/2007

Product Name: Sikadur Injection Gel / Anchor Fix 4 - Part B

CAS Number: Not Established

Chemical Family: Amine Compound

Chemical Formula: RMF-2945

MSDS Number: 4138

Product Code: 0786140

2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
AROMATIC HYDROCARBON BLEND	68477-31-6	
BENZYL ALCOHOL	100-51-6	
CALCIUM CARBONATE	471-34-1	
PROPRIETARY BLEND OF ALIPHATIC AND CYCLOALIPHATIC AMINES	Trade Secret	
TALC	14807-96-6	

Note: Exposure to Calcium Carbonate and Talc is applicable only if cured with Part "A" and sanded.

3. Hazards Identification

Eye Hazards

Causes eye irritation. Causes irreversible eye damage.

MATERIAL SAFETY DATA SHEET

Sikadur Injection Gel / Anchor Fix 4 - Part B

3. Hazards Identification - Continued

Skin Hazards

Causes skin irritation. Causes irreversible skin damage. Prolonged and/or repeated skin contact may cause an allergic reaction/sensitization.

Ingestion Hazards

May be harmful if swallowed.

Inhalation Hazards

Causes respiratory tract irritation.

4. First Aid Measures

Eye

In case of contact, hold eyelids apart and immediately flush eyes with plenty of tepid water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

Skin

In case of contact, immediately flush skin with soap and plenty of tepid water for at least 15 minutes. Get medical attention immediately if irritation (redness, rash, blistering) develops and persists.

Ingestion

If swallowed, do not induce vomiting unless directed to do so by medical personnel.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration.

5. Fire Fighting Measures

Flash Point: >200 °F

Autoignition Point: N/AV °F

Fire And Explosion Hazards

None known

Extinguishing Media

In case of fire, use water spray (fog) foam, dry chemical, or CO₂.

Fire Fighting Instructions

In the event of a fire, firefighters should wear full protective clothing and NIOSH-approved self-contained breathing apparatus with a full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

Avoid release to the environment. Use appropriate Personal Protective Equipment (PPE). Contain spill and collect with absorbent material and transfer into suitable containers. Do not flush to sewer or allow to enter waterways. Ventilate enclosed area.

7. Handling And Storage

Handling And Storage Precautions

Keep containers tightly closed. Keep out of reach of children.

Work/Hygienic Practices

Wash thoroughly with soap and water after handling.

8. Exposure Controls/Personal Protection

Engineering Controls

Use with adequate general and local exhaust ventilation. Refer to the current edition of "Industrial Ventilation: A Manual of Recommended Practice" published by the American Conference of Governmental Industrial Hygienists

MATERIAL SAFETY DATA SHEET

Sikadur Injection Gel / Anchor Fix 4 - Part B

8. Exposure Controls/Personal Protection - Continued

Engineering Controls - Continued

for information on the design, installation, use, and maintenance of exhaust systems.

Eye/Face Protection

Safety glasses with side shields or goggles.

Skin Protection

Chemical-resistant gloves. Lab coat or other work clothing. Launder before reuse.

Respiratory Protection

A respirator protection program that meets 29 CFR 1910.134 requirement must be followed whenever workplace conditions warrant a respirator's use. In areas where the Permissible Exposure Limits are exceeded, use a properly fitted NIOSH-approved respirator.

Other/General Protection

Wash thoroughly after handling.

Ingredient(s) - Exposure Limits

CALCIUM CARBONATE

ACGIH TLV-TWA 10 mg/m³

OSHA PEL-TWA 15 mg/m³

OSHA PEL-TWA 5 mg/m³

TALC

ACGIH TLV-TWA 2 mg/m³

OSHA PEL-TWA 20 mppcf

9. Physical And Chemical Properties

Appearance

Grey Paste

Odor

Amine Odor

Chemical Type: Mixture

Physical State: Solid

Melting Point: N/AV °F

Boiling Point: N/AV °F

Specific Gravity: 1.65

Percent Volatiles: N/AV

Packing Density: 13.81 pounds/gallon

Vapor Pressure: N/AV

Vapor Density: >AIR

Solubility: N/AV

VOC Content (A+B): < 105 grams/liter

10. Stability And Reactivity

Stability: Stable

Hazardous Polymerization: Will Not Occur

Conditions To Avoid (Stability)

Exotherms when curing in mass.

Incompatible Materials

Strong Oxidizers, acids, bases

MATERIAL SAFETY DATA SHEET

Sikadur Injection Gel / Anchor Fix 4 - Part B

10. Stability And Reactivity - Continued

Hazardous Decomposition Products

CO, CO₂, Oxides of Nitrogen, Ammonia

Conditions To Avoid (Polymerization)

Exotherms when curing in mass.

11. Toxicological Information

Ingredient(s) - Carginogenicity

TALC

Listed In The IARC Monographs

12. Ecological Information

No Data Available...

13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations. Waste generators must determine whether a discarded material is classified as a hazardous waste. USEPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

14. Transport Information

Proper Shipping Name

Not Regulated by the USDOT.

15. Regulatory Information

U.S. Regulatory Information

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

SARA Hazard Classes

Acute Health Hazard

Chronic Health Hazard

SARA Section 313 Notification

This product does not contain any ingredients regulated under Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 or 40 CFR 372.

Ingredient(s) - State Regulations

BENZYL ALCOHOL

New Jersey - Workplace Hazard

Pennsylvania - Workplace Hazard

Massachusetts - Hazardous Substance

CALCIUM CARBONATE

Pennsylvania - Workplace Hazard

TALC

New Jersey - Workplace Hazard

Pennsylvania - Workplace Hazard

Massachusetts - Hazardous Substance

MATERIAL SAFETY DATA SHEET

Sikadur Injection Gel / Anchor Fix 4 - Part B

16. Other Information

HMIS Rating

Health: *3

Fire: 1

Reactivity: 0

PPE: D

Revision/Preparer Information

MSDS Preparer: EHS Department

MSDS Preparer Phone Number: 201-933-8800

This MSDS Supercedes A Previous MSDS Dated: 12/19/2003

Disclaimer

The information contained in this Material Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Technical Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikacorp.com or 201-933-8800.

SIKA CORPORATION

Printed Using MSDS Generator™ 2000