



MATERIAL SAFETY DATA SHEET

Sikacem 103

HMIS

HEALTH	*2
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION	E

1. Product And Company Identification

Supplier

Sika Corporation
201 Polito Ave
Lyndhurst, NJ 07071

Company Contact: EHS Department
Telephone Number: 201-933-8800
FAX Number: 201-933-9379
Web Site: www.sikausa.com

Manufacturer

Sika Corporation
201 Polito Ave
Lyndhurst, NJ 07071

Company Contact: EHS Department
Telephone Number: 201-933-8800
FAX Number: 201-933-9379
Web Site: www.sikausa.com

Supplier Emergency Contacts & Phone Number

CHEMTREC: 800-424-9300
INTERNATIONAL: 703-527-3887

Manufacturer Emergency Contacts & Phone Number

CHEMTREC: 800-424-9300
INTERNATIONAL: 703-527-3887

Issue Date: 06/27/2006

Product Name: Sikacem 103
CAS Number: Not Established
Chemical Family: Cementitious Mortar
MSDS Number: 3932
Product Code: 0158540

2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
CEMENT, PORTLAND	65997-15-1	
SILICA, AMORPHOUS	7631-86-9	
SILICA, QUARTZ	14808-60-7	

3. Hazards Identification

Eye Hazards

May cause eye irritation.

Skin Hazards

Product becomes alkaline when exposed to moisture. May cause a reversible inflammatory effect on skin or tissue at the site of contact.

Ingestion Hazards

May be harmful if swallowed.

MATERIAL SAFETY DATA SHEET

Sikacem 103

3. Hazards Identification - Continued

Inhalation Hazards

Breathing dust may cause nose, throat or lung irritation. Respirable crystalline silica can cause silicosis, a fibrosis (scarring) of the lungs. Silicosis may be progressive.

4. First Aid Measures

Eye

In case of contact, hold eyelids apart and immediately flush eyes with plenty of tepid water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

Skin

In case of contact, immediately flush skin with soap and plenty of tepid water for at least 15 minutes. Get medical attention immediately if irritation (redness, rash, blistering) develops and persists.

Ingestion

If swallowed, do not induce vomiting unless directed to do so by medical personnel.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration, seek medical attention.

5. Fire Fighting Measures

Flash Point: >200 °F

Fire And Explosion Hazards

None known

Extinguishing Media

In case of fire, use water spray (fog) foam, dry chemical, or CO₂.

Fire Fighting Instructions

In the event of a fire, firefighters should wear full protective clothing and NIOSH-approved self-contained breathing apparatus with a full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

Avoid release to the environment. Using appropriate personal protective equipment (PPE), shovel material into waste containers taking care to minimize dust. Dampen if necessary to control dust. Vacuum clean dust with equipment fitted with High Efficiency Particulate Air (HEPA) filters.

7. Handling And Storage

Handling And Storage Precautions

Keep out of reach of children. Store in a cool, dry, well ventilated area. Keep containers tightly closed.

Work/Hygienic Practices

Wash thoroughly with soap and water after handling.

8. Exposure Controls/Personal Protection

Engineering Controls

Use of a system of local and/or general exhaust is recommended to keep employee below applicable exposure limits. Refer to the current edition of "Industrial Ventilation: A Manual of Recommended Practice" published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

Eye/Face Protection

Safety glasses with side shields or goggles.

MATERIAL SAFETY DATA SHEET

Sikacem 103

8. Exposure Controls/Personal Protection - Continued

Skin Protection

Chemical-resistant gloves. Lab coat or other work clothing to prevent skin exposure (Long sleeve shirt and long pants). Launder before reuse.

Respiratory Protection

A respirator protection program that meets 29 CFR 1910.134 requirement must be followed whenever workplace conditions warrant a respirator's use. In areas where the Permissible Exposure Limits are exceeded, use a properly fitted NIOSH-approved respirator.

Ingredient(s) - Exposure Limits

CEMENT, PORTLAND

ACGIH TLV-TWA - 10 mg/m³

OSHA PEL -TWA - 15 mg/m³ (total dust)

OSHA PEL - TWA - 5 mg/m³ (respirable dust)

SILICA, AMORPHOUS

ACGIH TLV-TWA 10 mg/m³

OSHA PEL-TWA 20 mppcf

OSHA PEL-TWA 80 / %SiO₂ mg/m³

SILICA, QUARTZ

ACGIH TLV-TWA 0.05 mg/m³ (Notice of Intended Change)

ACGIH TLV-TWA 0.025 mg/m³ (Proposed)

OSHA PEL-TWA 30/%SiO₂+2 mg/m³

OSHA PEL-TWA 10/%SiO₂+2 mg/m³

OSHA PEL-TWA 250/%SiO+5 mppcf

9. Physical And Chemical Properties

Appearance

Gray mortar

Odor

No odor

Chemical Type: Mixture

Physical State: Solid

10. Stability And Reactivity

Stability: STABLE

Hazardous Polymerization: WILL NOT OCCUR

Conditions To Avoid (Stability)

Contact of silica with powerful oxidizing agents such as fluorine, chlorine, trifluoride, manganese trioxide, oxygen difluoride, may cause fires. Upon direct contact with water, material will harden.

Incompatible Materials

None Known

Hazardous Decomposition Products

Silica will dissolve in hydrofluoric acid and produce a corrosive gas - silicon tetrafluoride.

Conditions To Avoid (Polymerization)

None known

MATERIAL SAFETY DATA SHEET

Sikacem 103

11. Toxicological Information

Ingredient(s) - Carcinogenicity

SILICA, AMORPHOUS

Listed In The IARC Monographs

SILICA, QUARTZ

NTP - Listed On The National Toxicology Program

Listed In The IARC Monographs

12. Ecological Information

No Data Available...

13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations. Waste generators must determine whether a discarded material is classified as a hazardous waste. USEPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

14. Transport Information

Proper Shipping Name

Not Regulated by the US DOT

15. Regulatory Information

U.S. Regulatory Information

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

SARA Hazard Classes

Acute Health Hazard

Chronic Health Hazard

SARA Section 313 Notification

This product does not contain any ingredients regulated under Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 or 40 CFR 372.

State Regulations

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects, or other reproductive harm.

Ingredient(s) - State Regulations

SILICA, AMORPHOUS

New Jersey - Workplace Hazard

Pennsylvania - Workplace Hazard

Massachusetts - Hazardous Substance

SILICA, QUARTZ

New Jersey - Workplace Hazard

Pennsylvania - Workplace Hazard

California - Proposition 65

Massachusetts - Hazardous Substance

16. Other Information

No Data Available...

MATERIAL SAFETY DATA SHEET

Sikacem 103

16. Other Information - Continued

HMIS Rating

Health: *2

Fire: 0

Reactivity: 0

PPE: E

Revision/Preparer Information

MSDS Preparer: EHS Deptmant

MSDS Preparer Phone Number: 201 933 8800

This MSDS Supercedes A Previous MSDS Dated: 06/27/2006

Disclaimer

The information contained in this Material Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Technical Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikacorp.com or 201-933-8800.

SIKA CORPORATION

Printed Using MSDS Generator™ 2000