



MATERIAL SAFETY DATA SHEET

Page 1 of 4

SIKADUR 330 US- Part B

HMIS

HEALTH	3
FLAMMABILITY	1
REACTIVITY	0
PERSONAL PROTECTION	D

1. Product And Company Identification

Supplier

Sika Corporation
201 Polito Ave
Lyndhurst, NJ 07071

Company Contact: EHS Department
Telephone Number: 201-933-8800
FAX Number: 201-933-9379
Web Site: www.sikausa.com

Manufacturer

Sika Corporation
201 Polito Ave
Lyndhurst, NJ 07071

Company Contact: EHS Department
Telephone Number: 201-933-8800
FAX Number: 201-933-9379
Web Site: www.sikausa.com

Supplier Emergency Contacts & Phone Number

CHEMTREC: 800-424-9300
INTERNATIONAL: 703-527-3887

Manufacturer Emergency Contacts & Phone Number

CHEMTREC: 800-424-9300
INTERNATIONAL: 703-527-3887

Issue Date: 01/19/2005

Product Name: SIKADUR 330 US- Part B
Chemical Family: Amines
MSDS Number: 3441
Product Code: 0333-001

2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
BLEND OF ALIPHATIC AMINES	Not Establis	

3. Hazards Identification

Eye Hazards

Corrosive to living tissue. Causes eye irritation. Causes eye burns.

Skin Hazards

Corrosive to living tissue. Contact with skin can cause irritation or burns. May cause skin sensitization.

Ingestion Hazards

Corrosive to living tissue. Harmful if swallowed.

Inhalation Hazards

Corrosive to living tissue. May cause burns.

4. First Aid Measures

Eye

In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

SIKADUR 330 US- Part B

4. First Aid Measures - Continued

Skin

In case of contact, immediately flush skin with soap and plenty of water for at least 15 minutes. Get medical attention immediately if irritation (redness, rash, blistering) develops and persists.

Ingestion

Dilute with water. Do not induce vomiting. Never give anything by mouth to an unconscious victim. Contact physician.

Inhalation

Remove to fresh air. If breathing has stopped, institute artificial respiration. Consult a physician.

5. Fire Fighting Measures

Flash Point: >200 °F

Autoignition Point: N/AV °F

Fire And Explosion Hazards

Exposure to heat builds up pressure in closed containers.

Extinguishing Media

In case of fire, use water spray (fog) foam, dry chemical, or CO₂.

Fire Fighting Instructions

In the event of a fire, firefighters should wear full protective clothing and NIOSH-approved self-contained breathing apparatus with a full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

Avoid release to the environment. Use appropriate Personal Protective Equipment (PPE). Contain spill and collect with absorbent material and transfer into suitable containers. Do not flush to sewer or allow to enter waterways. Ventilate enclosed area.

7. Handling And Storage

Handling And Storage Precautions

Keep out of reach of children. Store in a cool, dry, well ventilated area. Keep containers tightly closed.

Work/Hygienic Practices

Wash thoroughly with soap and water after handling.

8. Exposure Controls/Personal Protection

Engineering Controls

Use with adequate general and local exhaust ventilation. Refer to the current edition of "Industrial Ventilation: A Manual of Recommended Practice" published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

Eye/Face Protection

Faceshield over safety glasses or goggles.

Skin Protection

Avoid skin contact. Wear long sleeve shirt and long pants. Chemical resistant gloves.

Respiratory Protection

A respirator protection program that meets 29 CFR 1910.134 requirement must be followed whenever workplace conditions warrant a respirator's use.

Other/General Protection

Wash thoroughly after handling.

SIKADUR 330 US- Part B

<p>9. Physical And Chemical Properties</p> <p>Appearance Gray paste</p> <p>Odor Amine odor</p> <p>Chemical Type: Mixture Physical State: Liquid Specific Gravity: 1.20</p>
<p>10. Stability And Reactivity</p> <p>Stability: STABLE Hazardous Polymerization: WILL NOT OCCUR</p> <p>Conditions To Avoid (Stability) None Known</p> <p>Incompatible Materials Strong oxidizing agents, acid and epoxy resins under uncontrolled conditions.</p> <p>Hazardous Decomposition Products CO, CO₂, Oxides of nitrogen, ammonia.</p> <p>Conditions To Avoid (Polymerization) None Known</p>
<p>11. Toxicological Information</p> <p>No Data Available...</p>
<p>12. Ecological Information</p> <p>No Data Available...</p>
<p>13. Disposal Considerations</p> <p>Dispose in accordance with applicable federal, state and local government regulations. Waste generators must determine whether a discarded material is classified as a hazardous waste. USEPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.</p>
<p>14. Transport Information</p> <p>Proper Shipping Name Corrosive Liquid, basic, organic, n.o.s. (Aliphatic Amines)</p> <p>Hazard Class 8 PGIII</p> <p>DOT Identification Number UN3267</p> <p>DOT Shipping Label CORROSIVE</p>
<p>15. Regulatory Information</p> <p>U.S. Regulatory Information All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.</p>

MATERIAL SAFETY DATA SHEET

Page 4 of 4

SIKADUR 330 US- Part B

15. Regulatory Information - Continued

SARA Hazard Classes

Acute Health Hazard

SARA Section 313 Notification

This product does not contain any ingredients regulated under Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 or 40 CFR 372.

16. Other Information

HMIS Rating

Health: 3

Fire: 1

Reactivity: 0

PPE: D

Revision/Preparer Information

MSDS Preparer: EHS Department

MSDS Preparer Phone Number: 201-933-8800

Disclaimer

The data in this Material Safety Data Sheet relates only to the specific material herein and does not relate to use in combination with any other material or in any process. The information set forth herein is based on technical data that Sika believes to be reliable as of the date hereof. Since conditions of use are outside our control, we make no warranties, express or implied and assume no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under or a recommendation to infringe any patents.

SIKA CORPORATION